Change Loglevel for AADS Keycloak

To change the loglevel of AADS Keycloak Service do the following. As root User change the following File by adding Parameter: –log-level=<root-level>
/opt/Avaya/DeviceServices/<AADS-Versions>/CAS/10.2.0.1.16/service.d/keycloak.start.sh
Restart Keycloak Service In Case of Cluster Config all AADS Nodes need to be changed

The following Levels are available:

Level	Description
FATAL	Critical failures with complete inability to serve any kind of request.
ERROR	A significant error or problem leading to the inability to process requests.
WARN	A non-critical error or problem that might not require immediate correction.
INFO	Keycloak lifecycle events or important information. Low frequency.
DEBUG	More detailed information for debugging purposes, such as database logs. Higher frequency.
TRACE	Most detailed debugging information. Very high frequency.
ALL	Special level for all log messages.
OFF	Special level to turn logging off entirely (not recommended).

Example:

```
vi
/opt/Avaya/DeviceServices/10.2.0.1.16/CAS/10.2.0.1.16/service.d/keycloak.sta
rt.sh

$INSTALL_PARENT/keycloak-22.0.4/bin/kc.sh \
          start \
          --proxy edge \
          --hostname-path=/auth \
          **----log-level=DEBUG**
          ..
svc keycloak restart
```

Keycloak Source

From:
https://wiki.buergi.org/ - **Reto's WIKI**

Permanent link:
https://wiki.buergi.org/doku.php?id=avaya:aads:keycloak:debug&rev=1721969746

Last update: **2026/01/20 22:45**