

# Adaptation for Anonymous Calls

- 1. Regex Adaptation need to be activated on SM Global Setting
- 2. Create two Conditions

Commit Cancel

\* Condition Name: ANONYMOUS\_Contact  
 Notes:  
 Logical Operator: AND

**Operand 1**

\* Source Type: Request-Line  
 \* Source: Method  
 Instance:  
 Negative:  
 Expression: INVITE  
 Notes:

**Operand 2**

\* Source Type: Header  
 \* Source: Contact  
 \* Instance: any  
 Negative:  
 Expression: SWISSCOM\_ASM(1|2)  
 Notes:

Commit Cancel

and

**Condition Details**  
General

Commit Cancel

\* Condition Name: ANONYMOUS\_Publish  
 Notes:  
 Logical Operator: OR

**Operand 1**

\* Source Type: Request-Line  
 \* Source: Method  
 Instance:  
 Negative:  
 Expression: PUBLISH  
 Notes:

**Operand 2**

Source Type:  
 Source:  
 Instance:  
 Negative:  
 Expression:  
 Notes:

Commit Cancel

## 3. Create REGEX Adaptation with 2 Entries

**Regular Expression Adaptation Rule Details**  
General

Done Cancel

\* Rule Name: ANOYNMOUS\_INVITE\_incoming  
 Condition: ANONYMOUS\_Contact  
 \* Direction: Incoming  
 \* Order: 2  
 Notes:

**Rule Variables**

0 Items

Variable Name	Source Type	Source	Instance	Match Expression
---------------	-------------	--------	----------	------------------

**Rule Actions**

2 Items

Order	Source Type	Source	Instance	Operation	Match Expression	Replace / Add Expression
1	Header	Contact	any	modify	SWISSCOM_ASM(1 2)	Rufnummer unterdrueckt
2	Header	From	any	modify	^Anonymous\( .*)anonymous\@an	"Rufnummer unterdrueckt"\$(1)*"

Select : All, None

From:

<https://wiki.buergi.org/> - **Reto's WIKI**

Permanent link:

<https://wiki.buergi.org/doku.php?id=avaya:asm:anonymouse&rev=1731504636>

Last update: **2026/01/20 22:45**

